

24th World Congress on
Nanomaterials and Nanotechnology

July 12-13, 2018 Bangkok, Thailand

Theme: Expanding trends in the field of Nanomaterials and Nanotechnology

Novel hybrid Ga-SBA-3 nanostructured material: Synthesis, Characterization and Applications

Maria L. Martinez*, Marcos B. Gomez Costa, Andrea R Beltramone and Oscar A. Anunziata

Centro de Investigación en Nanociencia y Nanotecnología (NANOTEC), Facultad Regional Córdoba, Universidad Tecnológica Nacional, Maestro López y Cruz Roja Argentina, 5016, Córdoba, Argentina

In this work we study the incorporation of gallium in the structure of the SBA-3 mesoporous material, with the purpose of modifying the intrinsic acidity of the material using pyridine in order to determine the acidic sites that this material possesses.

In addition, studies of adsorption / desorption of aniline and its subsequent polymerization on the mesoporous Ga-SBA-3, that gives the unique hybrids compound, with conductive characteristics similar to those of an inorganic semiconductor. Si-SBA-3 was prepared using CTABr and TEOS, as surfactant and Si source respectively. To obtain Ga-SBA-3 post-synthesis incorporation was employed. Ga-SBA-3 were dehydrated at 400 ° C under vacuum and then were exposed to vapors of pyridine / liquid aniline depending on the studies to be performed (pyridine to determine the acid sites of the material and aniline for subsequent polymerization) at vacuum. The in-situ polymerization of aniline was carried out to produce PANI/Ga-SBA-3. The final PANI/Ga-SBA-3 material was characterized by XRD, ICP, SEM-EDX, FTIR, BET. Direct current electrical conductivity measurements were performed using pellets and a four-probe technique, improving the contacts with a gold layer. Higher amount of polyaniline in conductive emeraldine salt form was found in PANI/Ga-SBA-3 composite, with respect to other composites reported in the literature. At room temperature (273 K), the electrical conductivity of PANI/Ga-SBA-3 was 2.5×10^{-3} S/cm, higher than its of Al-SBA-3 and Al-MCM- 41 homologs. To explain the conductivity of the composite (nanowire of PANI within Ga-SBA-3), we must consider the configuration of the nanostructured material and the type of PANI anchoring.

Biography

Maria L. Marinez completed her doctorate at the age of 28 years of the Technological University and postdoctoral studies of the NANOTEC Center and the Bariloche Atomic Center (CAB) Argentina. She is currently a Scientific Researcher of CONICET-Argentina. She is director of several scientific and technological development projects. She has published more than 22 papers in prestigious journals and more than 80 presentations at international congresses and symposia.

Presenting author details

Full name: Maria L. Martinez

Contact number: 54 351 4690585

Session name: Nanochemistry

Category: Poster presentation